

TP-Link LS105G LiteWave 5-Port GB Desktop Switch



Code:
SWITP5302237

Vendor code:
LS105G

EAN code:
6935364085445

5-Port 10/100/1000Mbps Desktop Switch

Increase Your Network Speed and Save Energy

Let LiteWave Bring You Lighter Network Life

The TP-Link LiteWave Series Unmanaged Switches provide easy and affordable way to expand your wired network. They are easy to use and reliable. With these plug-and-play switches, you can expand your network connections to multiple devices instantly. With all ports support Auto-MDI/MDIX, there's no need to worry about the type of cable to use.

Go Green with Your Ethernet

The LiteWave Series also supports energy-efficient technology, helping you save power and money. Power consumption automatically adjusts according to link status and cable length, allowing you to expand your network while minimizing your carbon footprint. Save the planet and lower your energy bills — it's a win-win!

Durable Metal Casing

The interior components of LS105G are protected by high-quality metal casing to ensure a long product life. Having passed an array of stringent reliability tests, LS105G delivers switching performance you can depend on. Its

compact size makes it ideal for deployment on desktops or work benches.

Use Where You Need, However You Need

The LS105G is fully compatible with networked devices such as computers, printers, webcams, IPTVs. It has a wide range of application scenarios and is suitable for networking in school dormitories, surveillance, homes, and small businesses. - 10/100/1000Mbps Auto-Negotiation RJ45 port supporting Auto-MDI/MDIX- Green Ethernet technology saves power- IEEE 802.3X flow control provides reliable data transfer- Steel housing, desktop or wall-mounting design- Support 802.1p/DSCP QoS function- Plug and play, no configuration needed

Beheerfuncties

Switch type Unmanaged

Data-uitwisseling

Jumbo frames	16
Jumbo Frames ondersteuning	Ja
MAC-adrestabel	2000 entries
Packet buffergeheugen	1 MB
Verzending snelheid	7,4 Mpps

Design

Certificering	CE, FCC, RoHS
Kleur van het product	Blauw
Rack-montage	Nee

Eisen aan de omgeving

Luchtvochtigheid bij opslag	5 - 90 procent
Relatieve luchtvochtigheid, in bedrijf	10 - 90 procent
Temperatuur bij opslag	-40 - 70 °C
Temperatuur, in bedrijf	0 - 40 °C

Energie

AC invoer frequentie	50 Hz
AC invoer voltage	220 V
Vermogenstoever inclusief	Ja
Vermogensverbruik (max)	2,776 W

Gewicht en omvang

Breedte	99,8 mm
Diepte	98 mm
Hoogte	25 mm

Netwerk

10G support	Nee
Netwerkstandaard	IEEE 802.1p,IEEE 802.3ab,IEEE 802.3i,IEEE 802.3u,IEEE 802.3x

Poorten & interfaces

Aantal basis-switching RJ-45 Ethernet-poorten	5
Type basis-switching RJ-45 Ethernet-poorten	Gigabit Ethernet (10/100/1000)

Power over Ethernet (PoE)

Power over Ethernet (PoE)	Nee
---------------------------	-----