



D40A-1C5

Non-contact door switches, D40A, 1 aux output, 5m cable

Specifications

Door switch type	Non-contact
Guard-lock	✗
Coding	Basic
Material housing	PBT
Ambient temperature (operating)	-10-55 °C
Door contacts NC	1
Door contacts NO	1
LED indicator	✓
Connection method	Cable
Cable length	5 m
Cable exit direction	Bottom
Degree of protection (IP)	IP67
Output type	PNP
Shape	Cuboid
Overall length of sensor	13 mm
Height of sensor	48 mm
Width of sensor	25 mm
Switch without actuator	✗

CAD Library



D40A Instruction Instruction Manual

EN PDF 12.2 MB



D40A/G9SX-NS Non-Contact Door Switch/Flexible Safety Unit Datasheet

EN PDF 6.84 MB



EAC Mark removal Discontinuation Notice

EN PDF 221 KB



Machine Safety Catalogue

EN PDF 9.91 MB



Safety Component Selection Guide Brochure

EN PDF 7.57 MB



Safety Interlock Switches Brochure

EN PDF 1.52 MB



Safety Solution Advanced Guide Guide

EN PDF 2.57 MB



Safety Solution Basic Guide Guide

EN PDF 14.4 MB

TERMS OF WEBSITE USE

This PDF document was created from the European OMRON Industrial Automation website on 15 October, 2024. Click here for [terms of use](#).

OMRON

INDUSTRIAL AUTOMATION | [INDUSTRIAL.OMRON.EU](https://www.industrial.omron.eu)