


Item no.: 857-304  
 Product description: DC 24 V 10 MA RELAY WITH 1 CHANGEOVER CONTACT (1u) FOR AVERAGE SWITCH ABILITIES



Produkt kann von Bild abweichen / product may differ

Packing unit 1 piece

RoHS compliant

Nominal input voltage (Un) (DC)	DC 24 V
Current consumption at UN (20 °C)	10 mA
Contact material	AgSnO2
Input voltage range	Un -15 % ... +20 %
Max. switching frequency without load	20 s <sup>-1</sup>
Pull-in time (typ)	5 ms
Drop-out time (typ)	6 ms
Bounce time (typ)	5 ms
Dielectric strength contact / coil (kV)	4 kV
Dielectric strength open contact	1 kV
MAX. SWITCHING VOLTAGE	AC 250 V
Max. switching frequency with load	6 min <sup>-1</sup>
Normal operating method	100 % ED
nominal voltage per VDE 0110 section 1/4.97, IEC 60 664-1	250 V / 4 kV / 3
Mechanical life	5 x 10 <sup>6</sup> operations
Mechanical life at max. resistive load AC	5 x 10 <sup>4</sup> operations
Ambient operating temperature (Un)	-25 °C ... +60 °C
Storage temperature	-40 °C ... +70 °C
Cross section [mm <sup>2</sup> ]	0.08 - 2.5 mm <sup>2</sup>

Cross section [AWG]  
Connection method  
Weight

28 - 12 AWG  
CAGE CLAMP®S Connection  
29.8 g



Color	gray
Wiring type	Angled Type
No. of connection Points	5
No. of potentials	5
Height	81 mm
Height	3.189 in
Width	6 mm
Width	0.236 in
Depth	94 mm
Depth	3.701 in
Strip length from	9 mm
Strip length to	10 mm
Strip length	0.37 in
Country of Origin	Deutschland



Item no.	Admission office	Approval no.	Voltage [V]	Current [A]	Cross section [ mm <sup>2</sup> ]
857-304	GL	44 627 - 07 HH			
857-304	UL	E175199 Sec.4			

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected