


Omron Automation & Safety - U.S. Headquarters

2895 Greenspoint Parkway, Suite 200

Hoffman Estates, IL 60169

Tel: +1 (800) 556-6766, +1 (847) 843-7900

Fax: +1 (847) 843-7787

Email: info@omron.com
Item # E2E-X2D1-N 5M, E2E Series 2 mm Sensing Distance Proximity Sensor with 5 m Polyvinyl Chloride (PVC) Cable

PROX M8 2MM NO 5M


Specifications

Type	Proximity Sensor
Output Type	2-Wire Direct Current (DC)
Sensor Type	Inductive
Range	0 to 2 mm
DC Voltage	12 to 24 V
Accessories	Y92E-B8, Y92E-GS08, Y92E-GS08-SS, Y92E-GSB08, Y92E-ES08, Y92E-G08S, Y92E-G08S-T, Y92E-EG08-T, Y92E-CF08, Y92E-B08MT, Y92E-B08FRAS, Y92E-B08RAS, E39-VA
Spare Parts	M8-MHWS
Special Function	High-Quality Short Barrel Threaded Cylindrical Prox Conforms to Standard CENELC Sensing Distance.
Size	M8
Shield Type	Shielded

Polyvinyl Chloride (PVC) Cable Length	5 m
Contact Configuration	Normally Open (NO)
Case Material	Stainless Steel
Threaded Length	26 mm
Overall Length	37 mm
Mounting	Bracket with 8 mm Mounting Hole or M8x1 Threaded Hole
Mounting Hole Size	8 mm
Industry Standards	CENELC
Electrical Connection	5 m Polyvinyl Chloride (PVC) Cable
Sensing Distance	2 mm