



P2RF-08-PU

Socket, DIN rail/surface mounting, 15.5 mm, 8-pin, Push-in terminals

Specifications

Applicable product family	G2R-2-S, H3RN, K7L
Mounting method	DIN rail/screw
Product Depth (unpacked)	52.1 mm
Product Height (unpacked)	90 mm
Product Width (unpacked)	15.5 mm
Terminal type	Push-in Plus
Color	Black
Hold down clip included	✓
Release Lever included	✓

Fits to



G2R-2-S 110VAC (S)
Relay, plug-in, DPDT, 5 A,
mechanical indicator, 110
VAC



G2R-2-S 12VDC (S)
Relay, plug-in, 8-pin, DPDT,
10 A, mech indicator, label
facility, 12 VDC



G2R-2-S 220VAC (S)
Relay, plug-in, 5 A,
mechanical indicator, 220
VAC



G2R-2-S 230VAC (S)
Relay, plug-in, DPST, 10 A,
mechanical indicator, 230
VAC

**G2R-2-S 240VAC (S)**

Relay, plug-in, DPDT, 5 A, mechanical indicator, 240 VAC

**G2R-2-S 24VAC (S)**

Relay, plug-in, DPDT, 5 A, mechanical indicator, 24 VAC

**G2R-2-S 24VDC (S)**

Relay, plug-in, 8-pin, DPDT, 5 A, label facility, 24 VDC

**G2R-2-SD 24VDC (S)**

Relay, plug-in, 8-pin, DPDT, 5 A, mech indicators, coil suppressor, label facility

**G2R-2-SN 110VAC (S)**

Relay, plug-in, 8-pin, DPDT, 5 A, mech & LED indicators, label facility, 110 VAC

**G2R-2-SN 110VDC (S)**

Relay, plug-in, 8-pin, DPDT, 5 A, mech & LED indicators, label facility, 110 VDC

**G2R-2-SN 120VAC (S)**

Relay, plug-in, DPDT, 5 A, mech. & LED indicator, 120 VAC

**G2R-2-SN 12VAC (S)**

Relay, plug-in, 8-pin, DPDT, 5 A, mech & LED indicators, label facility, 12 VAC

**G2R-2-SN 12VDC (S)**

Relay, plug-in, 8-pin, DPDT, 5 A, mech & LED indicators, label facility, 12 VDC

**G2R-2-SN 230VAC (S)**

Relay, plug-in, 8-pin, DPDT, 5 A, mech & LED indicators, label facility, 230 VAC

**G2R-2-SN 240VAC (S)**

Relay, plug-in, DPDT, 5 A, mech. & LED indicator, 240 VAC

**G2R-2-SN 24VAC (S)**

Relay, plug-in, 8-pin, DPDT, 5 A, mech & LED indicators, label facility, 24 VAC

**G2R-2-SN 24VDC (S)**

Relay, plug-in, 8-pin, DPDT, 5 A, mech & LED indicators, label facility, 24 VDC

**G2R-2-SN 48VAC**

Relay, plug-in, 8-pin, DPDT, 5 A, mech & LED indicators, label facility, 48 VAC

**G2R-2-SN 48VDC (S)**

Relay, plug-in, 8-pin, DPDT, 5 A, mech & LED indicators, label facility, 48 VDC

**G2R-2-SN-AP3 24VDC (S)**

Relay, plug-in, 8-pin, DPDT, 5 A, gold-plated contacts, LED indicator



G2R-2-SND 12VDC (S)
Relay, plug-in, 8-pin, DPDT, 5 A, mech & LED indicators, coil suppressor, label facility, 12 VDC



G2R-2-SND 24VDC (S)
Relay, plug-in, 8-pin, DPDT, 5 A, mech & LED indicators, coil suppressor, label facility



G2R-2-SND 48VDC (S)
Relay, plug-in, 8-pin, DPDT, 5 A, mech & LED indicators, coil suppressor, label facility, 48 VDC



G2R-2-SND-AP3 24VDC (S)
Relay, plug-in, 8-pin, DPDT, 5 A, gold-plated contacts, mech & LED indicators, coil suppressor, label facility



G2R-2-SNDI 12VDC (S)
Relay, plug-in, 8-pin, DPDT, 5 A, mech & LED indicators, coil suppressor, lockable test button, label facility, 12 VDC



G2R-2-SNDI 24VDC (S)
Relay, plug-in, 8-pin, DPDT, 5 A, mech & LED indicators, coil suppressor, lockable test button, label facility



G2R-2-SNDI 48VDC (S)
Relay, plug-in, 8-pin, DPDT, 5 A, mech & LED indicators, coil suppressor, lockable test button, label facility



G2R-2-SNDI-AP3 24VDC (S)
Relay, plug-in, 8-pin, DPDT, 5 A, mech & LED indicators, coil suppressor, label test button, Au-plating



G2R-2-SNI 110VAC (S)
Relay, plug-in, 8-pin, DPDT, 5 A, mech & LED indicators, lockable test button, label facility



G2R-2-SNI 120VAC (S)
Relay, plug-in, DPDT, 5 A, mech. & LED indicator, test button, 120 VAC




G2R-2-SNI 12VAC (S)
Relay, plug-in, 8-pin, DPDT, 5 A, mech & LED indicators, lockable test button, label facility



G2R-2-SNI 12VDC (S)
Relay, plug-in, 8-pin, DPDT, 5 A, mech & LED indicators, lockable test button, label facility, 12 VDC



G2R-2-SNI 230VAC (S)
Relay, plug-in, 8-pin, DPDT, 5 A, mech & LED indicators, lockable test button, label facility



G2R-2-SNI 240VAC (S)
Relay, plug-in, DPDT, 5 A, mech. & LED indicator, test button, 240 VAC



G2R-2-SNI 24VAC (S)
Relay, plug-in, 8-pin, DPDT, 5 A, mech & LED indicators, lockable test button, label facility



G2R-2-SNI 24VDC (S)
Relay, plug-in, 8-pin, DPDT, 5 A, mech & LED indicators, lockable test button, label facility



G2R-2-SNI 48VAC (S)
Relay, plug-in, 8-pin, DPDT, 5 A, mech & LED indicators, lockable test button, label facility



G2R-2-SNI 48VDC (S)
Relay, plug-in, 8-pin, DPDT, 5 A, mech & LED indicators, lockable test button, label facility



G2R-2-SNI-AP3 230VAC (S)
Relay, plug-in, DPDT (gold plated), 5 A, mech. & LED indicator, test button, 230 VAC

Accessories



PFP-100N

DIN-rail mounting track, 35 x 7.3 mm, 1 m length



PFP-100N2

DIN-rail mounting track, 35x16mm, 1m length



PFP-50N

Din rail track, 500 mm



PFP-M

End plate



PFP-S

Spacer



PYDN-15.5-080R

Accessory for PYF-PU, 15.5mm pitch, 8 Poles, Red color



PYDN-15.5-080S

Accessory for PYF-PU, 15.5mm pitch, 8 Poles, Blue color



PYDN-15.5-080Y

Accessory for PYF-PU, 15.5mm pitch, 8 Poles, Yellow color



PYDN-7.75-020R

Accessory for PYF-PU/P2RF-PU, 7.75mm pitch, 2 Poles, Red color




PYDN-7.75-020S

Accessory for PYF-PU/P2RF-PU, 7.75mm pitch, 2 Poles, Blue color



PYDN-7.75-020Y

Accessory for PYF-PU/P2RF-PU, 7.75mm pitch, 2 Poles, Yellow color




PYDN-7.75-030R

Accessory for PYF-PU/P2RF-PU, 7.75mm pitch, 3 Poles, Red color




PYDN-7.75-030S

Accessory for PYF-PU/P2RF-PU, 7.75mm pitch, 3 Poles, Blue color



PYDN-7.75-030Y

Accessory for PYF-PU/P2RF-PU, 7.75mm pitch, 3 Poles, Yellow color




PYDN-7.75-040R

Accessory for PYF-PU/P2RF-PU, 7.75mm pitch, 4 Poles, Red color



PYDN-7.75-040S

Accessory for PYF-PU/P2RF-PU, 7.75mm pitch, 4 Poles, Blue color



PYDN-7.75-040Y

Accessory for PYF-PU/P2RF-PU, 7.75mm pitch, 4 Poles, Yellow color



PYDN-7.75-200R

Accessory for PYF-PU/P2RF-PU, 7.75mm pitch, 20 Poles, Red color



PYDN-7.75-200S

Accessory for PYF-PU/P2RF-PU, 7.75mm pitch, 20 Poles, Blue color



PYDN-7.75-200Y

Accessory for PYF-PU/P2RF-PU, 7.75mm pitch, 20 Poles, Yellow color



XW5Z-EP12

Separator Plate for terminal blocks, 12 mm width



XW5Z-EP6

End bracket for terminal blocks, 6 mm width

CAD Library



EAC Mark removal Discontinuation Notice

EN PDF 221 KB



PYF-___-PU/PTF-___- PU/P2RF-___-PU Sockets with Push-In Plus technology Datasheet

EN PDF 2.59 MB